



# JABLOTRON ALARMS NEWS ALERT

September 2008

## In this issue:

- *CT-01 detector*
- *RP-01 system*
- *Training 2008*
- *Upcoming exhibitions*

## Recommended Links:

*Jablotron Alarms a.s.*

*Oasis system*

*Oasis training - dates & details*

*Nanny Baby Breath Monitor*

## Contact Us:

**Jablotron Alarms a.s.**

Pod Skalkou 33  
46601 Jablonec nad Nisou  
Czech Republic

### **Sales:**

Tel. +420 483 559 966  
Tel. +420 483 559 995  
Fax +420 483 559 993  
[export@jablotron.cz](mailto:export@jablotron.cz)


### **Technical Support:**

Tel. +420 483 559 940  
[support@jablotron.cz](mailto:support@jablotron.cz)

If you have any comments or wishes regarding *Jablotron Alarms News Alert*, please do not hesitate to contact the editor Mr. Mike Williams: [williams@jablotron.cz](mailto:williams@jablotron.cz)

If your colleagues or friends would like to receive *Jablotron Alarms News Alerts*, send us their Email addresses to be added to the mailing list.

If you do not wish to receive *Jablotron News* in future, please reply to this e-mail with "Remove" as the subject.



## The CT-01 wired shutter-movement detector

The CT-01 is wired detector for detecting the unauthorised movement of external window shutters on houses or buildings.

In practice the CT-01 wired outputs are connected to the wired input of a JA-80MI door detector to connect the CT-01 signals to the Oasis alarm system.

False alarms caused by the wind moving the shutters are avoided by the door detector only raising the alarm when at least 3 pulses are received from the CT-01 in 10 seconds.

Please contact our Export Department for price and delivery info.

## The RP-01 access control system

The RP-01 is an independent access control system for those looking for a simple value-for-money system which is easy to set up.

The output relay (1A/125V) can be connected to an electric lock to open a door when one of 999 possible access cards or tags are presented to the reader unit.

The RFID reader unit accepts cards built to the common Unique 125 kHz standard, e.g. Jablotron Alarms' PC-01 and PC-02.

The system runs off 9-16 V DC or 8-12V AC and the relay output offers 1-9 second pulses or toggling (on-off-on....) each time a card is presented. For those who prefer to use a PC for the set up, there is also suitable software available.

Please contact our Export Department for price and delivery info.



## Training 2008

Each Oasis training course provides 2 days of technical training for distributors and installers. Subjects covered include marketing strategy and installation techniques. The aim is for successful participants to become certified installers and trainers. Training is provided free of charge and is limited to 12 people per training course. Please contact Jablotron Alarms' Export Sales Department to register yourself.

### Dates:

18. - 19.9.2008  
23. - 24.10.2008  
4. - 5.12. 2008

Contact the Export department to register yourself.



A training course in action

## Upcoming exhibitions

We warmly invite you to visit our stands at the following exhibitions:

(click on the events below for more info)

16 – 20 Sept: International Trade Fair Zagreb

7 – 10 Oct: Security 2008 in Essen, Germany

15 – 18 Oct: Sfitex, Russia

21 – 24 October: Bezpeka, Kiev, Ukraine

